

Data Sheet

FUJITSU Server PRIMERGY TX100 S3p Tower Server

Enter the world of PRIMERGY TX servers

Fujitsu Server PRIMERGY TX Tower Servers are ideal for use in SMEs or branch offices. They increase operational efficiency by providing rock solid, record-breaking, energy efficient performance. That performance is built on 20-years of pioneering work in Green IT. As a customer, you benefit from a reduction in your organization's environmental impact and lower running costs. The reliability is proven by testing the machines through 5000 boot cycles – far more than other vendors do. PRIMERGY TX servers are also easy to manage via the PRIMERGY ServerView Suite, reducing IT admin workload and costs. Plus, tower to rack conversion kits are available for most TX systems, ensuring investment protection.

PRIMERGY TX100 S3p

The Fujitsu Server PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. With a maximum of 32 GB of RAM, and excellent processor performance, it offers more than enough performance for all classic server tasks, such as file, print, web or office applications. The dual onboard gigabit LAN, makes it easier to do business 24x7. Moreover, the TX100 S3p is incredibly silent making it an excellent choice for any office environment. With its optional 0-Watt functionality and a choice of two highly efficient power supply units, the TX100 S3p minimizes costs and the environmental impact.



Features & Benefits

Main Features	Benefits
<ul style="list-style-type: none">■ An excellent first server for SMEs looking for Intel® Xeon® support and up to 32 GB of RAM■ Choose between a power supply unit (PSU) with 85% efficiency or with 94% energy efficiency and 0-Watt functionality■ Effective air flow design for low noise levels■ Dual onboard gigabit LAN, ECC memory and optional SATA RAID 5/6 with FBU■ Halogen-free printed circuit board	<ul style="list-style-type: none">■ Great price-performance ratio - ideal for all classic server tasks like file, print, web or office applications■ Benefit from Fujitsu's pioneering experience in Green IT - save money and minimize the environmental impact■ Silent system for an ergonomic working environment■ Keep business processes going - 24x7■ For environmentally friendly waste disposal

Technical details

PRIMERGY TX100 S3p

Housing types	Tower	Tower
Storage drive architecture	4x 3.5-inch SATA	4x 3.5-inch SATA
Power supply	Standard	Standard (0-Watt)

Mainboard

Mainboard type	D 3009
Chipset	Intel® C202
Processor quantity and type	1 x Intel® Celeron® processor / Intel® Pentium® processor / Intel® Core™ i3 processor / Intel® Xeon® processor E3-1200v2 product family

Processor	Intel® Celeron® processor G1610 (2C/2T, 2.60 GHz, TLC: 2 MB, Turbo: No, 1333 MHz, 55 W)
	Intel® Core™ i3-3220 processor (2C/4T, 3.30 GHz, TLC: 3 MB, Turbo: No, 1600 MHz, 55 W)
	Intel® Pentium® processor G2120 (2C/2T, 3.10 GHz, TLC: 3 MB, Turbo: No, 1600 MHz, 55 W)
	Intel® Xeon® processor E3-1220v2 (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
	Intel® Xeon® processor E3-1230v2 (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
	Intel® Xeon® processor E3-1240v2 (4C/8T, 3.40 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)

Memory slots	4
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	2 GB - 32 GB
Memory protection	ECC

Memory options	4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Memory modules notes	Only UDIMM (unbuffered) supported
----------------------	-----------------------------------

Interfaces

USB 2.0 ports	9
Graphics (15-pin)	1 x VGA (ATI ES1000 (64MB) on board)
Serial 1 (9-pin)	1 x RS232
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet

I/O controller on board

Serial ATA total	6
RAID controller	4 port SATA with RAID 0/1/10 for HDDs
SATA Controller	Intel® C202
LAN Controller	Intel® 82574L + Intel® 82579LM onboard, 2 x 10/100/1000 Mbit/s Ethernet, PXE-Boot by LAN via PXE-Server, Teaming supported
Trusted Platform Module (TPM)	Infineon / 1.2 (option)

Slots

PCI-Express 3.0 x8	1 x
PCI-Express 3.0 x8 (mech. x16)	1 x
PCI-Express 2.0 x1 (mech. x4)	1 x notched for x16 cards
PCI-Express 2.0 x4	1 x notched for x16 cards
Slot Notes	In configurations with Intel® Core™ i3 or Intel® Pentium® processors slots are operated with PCI-Express 2.0.

Drive bays

Storage drive bay configuration	4x 3.5" easy change SATA
---------------------------------	--------------------------

Drive bays

Notes accessible drives	2 (1 bay is occupied by DVD/DVD-RW, 3.5-inch)
-------------------------	---

General software information

Fan configuration	Silent system fans
-------------------	--------------------

Fan notes	Non hot-plug
-----------	--------------

Operating panel

Operating buttons	On/off switch
-------------------	---------------

Status LEDs	Power (green)
-------------	---------------

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server R2 2012
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Windows Server® 2012 R2 Essentials
	Microsoft® Windows Server® 2012 R2 Foundation
	Microsoft® Windows Storage Server 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Server® 2012 Essentials
	Microsoft® Windows Server® 2012 Foundation
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows Server® 2008 R2 Foundation
	Microsoft® Windows® Web Server 2008 R2
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
Microsoft® Windows® Server 2008 Enterprise	
Microsoft® Windows® Server 2008 Standard	
Novell® SUSE Linux Enterprise Server 11	
Novell® SUSE Linux Enterprise Server 10	
Red Hat® Enterprise Linux 6	
Red Hat® Enterprise Linux 5	

Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
-------------------------------	---

Operating system notes	Support of other Linux derivatives on demand Red Hat® certification starting with version 5.8 / 6.4.
------------------------	---

Server Management

Standard	ServerView Suite - Deploy SV Installation Manager
----------	--

Option	ServerView Suite - Deploy SV Deployment Manager (full version) ServerView Suite - Integrate SV Integration pack for Fujitsu ManageNow® solution
--------	--

Server Management notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.
-------------------------	---

Dimensions / Weight

Floor-stand (W x D x H)	175 x 419 x 395 mm
-------------------------	--------------------

Weight	up to 14 kg
--------	-------------

Environmental

Operating ambient temperature	10 - 35 °C
-------------------------------	------------

Environmental

Operating temperature note	ETSI 300 019-2-3 Class 3.1
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	According to ISO9296
Sound pressure (LpAm)	23 dB(A) (idle)/ 24 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	4.0B (idle)/ 4.0B (operating)
Noise notes	Noise emissions and operation modes depend on system configuration.

Electrical values

Power supply configuration	1
Power supply efficiency	85 % (80 PLUS bronze) 94 % (80 PLUS platinum)
Standard power supply output	250 W
Rated voltage range	100 V - 127 V / 200 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	100 V – 240 V / 5.0 – 2.5 A
Rated current in basic configuration	100 V – 240 V / 1,5 – 0,6 A
Active power (min. configuration)	22 W
Active power (max. configuration)	209 W
Active power note	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: http://configurator.ts.fujitsu.com/public/
Apparent power (max. configuration)	211 VA
Heat emission	752.4 kJ/h (713.1 BTU/h)
Power Supply Notes	Fujitsu patented 0-Watt standby technology (optional).

Compliance

Germany	GS
Europe	CE Class A * ENERGY STAR® (with standard power supply unit)
USA/Canada	CSA us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) ENERGY STAR® (with 0-Watt power supply unit)
Japan	VCCI Class A
South Korea	KC
China	CCC
Australia/New Zealand	C-Tick (AS / NZS CISPR 22 Class A)
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Global	
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates http://globalsp.ts.fujitsu.com/sites/certificates

Components

Storage drives	HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, non hot plug, 3.5-inch, economic
	HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 250 GB, 7200 rpm, non hot plug, 3.5-inch, economic
	HDD SATA, 6 Gb/s, 3 TB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7200 rpm, non hot plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7200 rpm, non hot plug, 3.5-inch, business critical
Backup Drives	DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-ROM ; 8x DVD; 24x CD), slimline, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
RAID Controller	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116C), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
Communication, Network	Ethernet Ctrl. 1 x 1 Gbit/s PCIe x1 (Intel®)
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe x4 (Fujitsu)
Graphics add on cards	NVIDIA® Quadro® NVS 300, PCIe x1, 2x DVI/VGA
Warranty	
Standard Warranty	1 year
Service level	Onsite Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM
Maintenance and Support Services - the perfect extension	
Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
Recommended Service	24x7, Onsite Response Time: 4h
Service Lifecycle	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX100 S3p, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX100 S3p, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2014-01-16 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions